## MODEL

### **Description**

Multi axis transducer Model MAT - 200 is multi axis force sensor designed for measuring the force in the lathe operation. It exhibits high sensitivity with low cross talk & excellent repeatability. This is strain gage based sensor with full temperature compensation over 10 to 60°C. This is available with three axis force sensing in X, Y & Z directions. This is designed & manufactured as per customer's requirement.

#### **Features**

- · Multi axis force and torque combination available.
- Available in various capacities, ranging from 0 100 N to 0 20000 N  $\,$ for force & 0 - 100 NM to 0 - 1000 NM for torque.
- Can be provided in various shapes like Rectangular, Cylindrical, Platform or Flanged

# **Applications**

Lathe Operation Cutting Force Dynamometer Material Testing Grinding & abrasive Wheel Research Tool Wear research Automotive Research


# Performance Specification


Performance Specification		
Standard Capacity	Force	X, Y - 5 KN Z - 20 KN
Excitation Voltage		10 VDC- Maximum 15 VDC
Nominal Output	Force	1 to 1.5 mV/V in X & Y axis 1 - 1.5mV/V in Z axis
Non - Linearity		< ±0.5% FSO (Full Scale Output)
Hysteresis		< ±0.5% FSO
Cross Talk		$ Fz \rightarrow Fx, \ Fy - 1\% \\ Fx \leftrightarrow Fy - 2\% \\ Fx, Fy \rightarrow Fz - 3\% $
Non-Repeatability		< ±0.2% FSO
Creep (30 minutes)		< ±0.05% FSO
Zero Balance		±1.0% FSO
Bridge Resistance		350 / 700 ± 20 Ohms
Insulation Resistance (50 VDC)		> 2000 Mega Ohms
Cable Length (8 Core)		5 Meters
Safe Overload of Rated Capacity		150%
Ultimate Overload of Rated Capacity		200%
Temp. Compensated Range		10-60 <sup>0</sup> C
Operating Temperature		0 - 90°C
Temperature Effect on Output		< 0.05% FSO/ °C
Temperature Effect on Zero		< 0.05% FSO/ °C
Finish & Construction		Electroless Nickel plated Tool Steel
Environmental Protection Class		IP65

# **Electrical Termination**

8 core cable for Excitation: 2 core X, Y, Z Force: 6 cores







Manufactured by:



917/1, G.I.D.C. Estate, Makarpura Vadodara - 390 010. Gujarat, INDIA

Ph : +91-265-2655083, 2651023

: +91-265-2638751 Fax

8 Pin Connector

: +91-9374068998, 9327425560 Email : sales@adiartech.com, adiartech@adiartech.com

Website: www.adiartech.com